

WT69 (R-469A)

Dampfdrucktabelle

Druck (bar)	Temperatur (°C)		Dichte (kg/m ³)		Enthalpie (kJ/kg)		Entropie (kJ/kg-K)	
	flüssig	gasförmig	flüssig	gasförmig	flüssig	gasförmig	flüssig	gasförmig
0,50	-90,22	-73,33	1399,5	1,813	54,53	398,65	0,36341	2,15980
1,00	-78,73	-61,75	1364,0	3,468	72,23	405,32	0,45704	2,09710
1,50	-71,18	-54,21	1340,1	5,072	83,89	409,47	0,51570	2,06130
2,00	-65,40	-48,46	1321,5	6,649	92,86	412,49	0,55931	2,03630
2,50	-60,63	-43,76	1305,9	8,208	100,28	414,87	0,59440	2,01700
3,00	-56,55	-39,75	1292,4	9,754	106,66	416,83	0,62396	2,00140
3,50	-52,95	-36,23	1280,3	11,297	112,30	418,48	0,64961	1,98810
4,00	-49,72	-33,08	1269,3	12,832	117,38	419,91	0,67236	1,97670
4,50	-46,78	-30,23	1259,2	14,363	122,03	421,15	0,69284	1,96670
5,00	-44,07	-27,60	1249,8	15,897	126,32	422,26	0,71152	1,95760
5,50	-41,56	-25,18	1240,9	17,429	130,32	423,24	0,72871	1,94940
6,00	-39,21	-22,92	1232,6	18,959	134,07	424,13	0,74467	1,94190
6,50	-37,01	-20,80	1224,6	20,495	137,62	424,92	0,75957	1,93500
7,00	-34,92	-18,80	1217,0	22,035	140,98	425,65	0,77357	1,92860
7,50	-32,94	-16,91	1209,8	23,577	144,18	426,30	0,78678	1,92260
8,00	-31,06	-15,12	1202,8	25,119	147,24	426,90	0,79931	1,91690
8,50	-29,26	-13,41	1196,0	26,672	150,18	427,45	0,81122	1,91160
9,00	-27,53	-11,77	1189,5	28,227	153,00	427,95	0,82259	1,90650
9,50	-25,88	-10,21	1183,2	29,785	155,73	428,41	0,83346	1,90170
10,00	-24,28	-8,70	1177,0	31,354	158,36	428,83	0,84390	1,89700
10,50	-22,74	-7,25	1171,1	32,927	160,90	429,21	0,85393	1,89260
11,00	-21,26	-5,85	1165,2	34,506	163,37	429,56	0,86359	1,88840
11,50	-19,82	-4,51	1159,5	36,089	165,77	429,88	0,87292	1,88430
12,00	-18,43	-3,20	1154,0	37,685	168,11	430,18	0,88194	1,88030
12,50	-17,08	-1,94	1148,5	39,283	170,38	430,44	0,89068	1,87650
13,00	-15,76	-0,72	1143,1	40,892	172,60	430,68	0,89915	1,87280
13,50	-14,48	0,47	1137,9	42,511	174,77	430,90	0,90738	1,86920
14,00	-13,24	1,63	1132,7	44,136	176,89	431,10	0,91538	1,86570
14,50	-12,03	2,75	1127,7	45,767	178,96	431,27	0,92317	1,86230
15,00	-10,84	3,85	1122,7	47,409	180,99	431,43	0,93076	1,85900
15,50	-9,69	4,91	1117,7	49,064	182,98	431,57	0,93816	1,85580
16,00	-8,56	5,95	1112,9	50,722	184,93	431,69	0,94538	1,85260
16,50	-7,45	6,97	1108,1	52,393	186,85	431,79	0,95245	1,84950
17,00	-6,37	7,96	1103,4	54,076	188,74	431,88	0,95935	1,84650
17,50	-5,31	8,93	1098,7	55,767	190,59	431,95	0,96611	1,84350
18,00	-4,27	9,88	1094,1	57,468	192,41	432,01	0,97274	1,84060
18,50	-3,26	10,81	1089,5	59,180	194,21	432,05	0,97923	1,83770

WT69 (R-469A)

Dampfdrucktabelle

Druck (bar)	Temperatur (°C)		Dichte (kg/m ³)		Enthalpie (kJ/kg)		Entropie (kJ/kg-K)	
	flüssig	gasförmig	flüssig	gasförmig	flüssig	gasförmig	flüssig	gasförmig
19,00	-2,26	11,72	1085,0	60,903	195,97	432,08	0,98559	1,83490
19,50	-1,28	12,61	1080,5	62,637	197,72	432,09	0,99184	1,83210
20,00	-0,32	13,48	1076,0	64,383	199,43	432,10	0,99798	1,82930
20,50	0,63	14,34	1071,6	66,141	201,13	432,09	1,00400	1,82660
21,00	1,56	15,18	1067,3	67,910	202,80	432,06	1,00990	1,82400
21,50	2,47	16,00	1062,9	69,692	204,45	432,03	1,01580	1,82130
22,00	3,37	16,81	1058,6	71,486	206,08	431,98	1,02150	1,81870
22,50	4,26	17,61	1054,3	73,294	207,70	431,92	1,02720	1,81620
23,00	5,13	18,39	1050,1	75,114	209,29	431,86	1,03270	1,81360
23,50	5,99	19,16	1045,9	76,948	210,87	431,78	1,03820	1,81110
24,00	6,83	19,91	1041,7	78,796	212,43	431,69	1,04360	1,80860
24,50	7,66	20,66	1037,5	80,658	213,97	431,59	1,04900	1,80610
25,00	8,48	21,39	1033,4	82,534	215,50	431,48	1,05420	1,80360