

Trade name: R410A

Product no.: R410A

Current version : 3.0.0, issued: 11.01.2022

Replaced version: 2.0.0, issued: 29.03.2021

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

R410A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Industrial Use

Professional use

Refrigerant

Uses advised against

Consumer use

1.3 Details of the supplier of the safety data sheet

Address

TEGA - Technische Gase und Gasetechnik GmbH

Werner-von-Siemens-Straße 18

97076 Würzburg

Telephone no. +49 931 2093-220

Fax no. +49 931 2093-180

e-mail kaeltemittel@tega.de

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Press. Gas liq.; H280

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS04

Signal word

Warning

Hazard statement(s)

H280

Contains gas under pressure; may explode if heated.

Trade name: R410A**Product no.:** R410A**Current version :** 3.0.0, issued: 11.01.2022**Replaced version:** 2.0.0, issued: 29.03.2021**Region:** GB**Precautionary statement(s)**

P410+P403 Protect from sunlight. Store in a well-ventilated place.

Supplemental label elements

Contains fluorinated greenhouse gases (HFC-125, HFC-32).

2.3 Other hazards

Danger of suffocation by displacement of air / oxygen. Contact with the liquid can cause cold burns or frostbite. Please observe the information given in this safety data sheet.

PBT assessment

The product is not considered to be a PBT.

vPvB assessment

The product is not considered to be a vPvB.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	pentafluoroethane		
	354-33-6 206-557-8 - 01-2119485636-25	Press. Gas liq.; H280	>= 50.00 - < 70.00 Vol%
2	difluoromethane		
	75-10-5 200-839-4 - 01-2119471312-47	Flam. Gas 1A; H220 Press. Gas liq.; H280	>= 50.00 - < 70.00 Vol%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

SECTION 4: First aid measures**4.1 Description of first aid measures****General information**

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove affected person from danger area, lay him down. Seek medical advice immediately.

After inhalation

Remove affected persons from dangerous area by observing suitable respiratory protection measures. Ensure supply of fresh air. Irregular breathing/no breathing: artificial respiration. Call a doctor immediately.

After skin contact

In case of contact with skin wash off immediately with soap and water. Rinse with much water in case of frostbites. Remove clothes only after unfreezing. Cover wounds with sterile dressing. Call a doctor immediately.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Trade name: R410A**Product no.:** R410A**Current version :** 3.0.0, issued: 11.01.2022**Replaced version:** 2.0.0, issued: 29.03.2021**Region:** GB**Symptoms**

The following symptoms may occur: respiratory arrest. Shortness of breath; Light-headedness; muscle incoordination; Unconsciousness; cardiac arrhythmia; Dizziness; confusion; anesthetic effect; Skin irritation; red eyes; nausea; frostbite; Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Do not administer any preparations of the adrenaline-ephedrine group.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

recommended: alcohol resistant foam, CO₂, powders, water spray/mist; Extinguishing measures to suit surroundings.

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide and carbon dioxide; Hydrogen fluoride (HF); Carbonyl fluoride; fluorine compounds; Liquefied gas: Spilled liquid can cause cold burns. This gas is heavier than air and may accumulate in low areas.

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear full protective suit. Containers close to fire should be transferred to a safe place. Cool closed containers exposed to fire with water. Pressure increase, bursting and explosion hazard during heating. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Provide good room ventilation even at ground level (vapours are heavier than air). Do not breathe gas. Keep away from ignition sources. Use personal protective clothing. Cordon and mark contaminated area. Remove persons to safety.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Avoid release in the environment. Suppress gases/vapours/mists with water spray jet.

6.3 Methods and material for containment and cleaning up

Ensure adequate ventilation. Dispose of absorbed material in accordance with the regulations.

6.4 Reference to other sections

Information regarding safe handling, see section 7. Information regarding personal protective measures, see section 8. Information regarding waste disposal, see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Advice on safe handling**

Only qualified and trained persons are authorised to handle. Provide good ventilation at the work area (local exhaust ventilation, if necessary). To be used only according to instructions for use. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose containers heat or sources of ignition. In case of accidental release: danger due to low temperature of the liquid product. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Comply with the

Trade name: R410A

Product no.: R410A

Current version : 3.0.0, issued: 11.01.2022

Replaced version: 2.0.0, issued: 29.03.2021

Region: GB

health and safety at work laws.

General protective and hygiene measures

Wash hands before breaks and after work. Do not inhale gases. Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Have emergency shower available.

Advice on protection against fire and explosion

The product is not combustible. The substance can form a combustible mixture with air at elevated pressure. Isolate from sources of heat, sparks and open flame. Take precautionary measures against electrostatic loading (earthing necessary during loading operations). Electrical equipment should be protected to the appropriate standard.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Keep container tightly closed in a cool, well-ventilated place, open and handle carefully. Protect from heat and direct sunlight.

Recommended storage temperature

Value < 50 °C

Storage stability

Comments When stored properly, the storage life is unlimited.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

Substances to be avoided, see section 10.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****DNEL, DMEL and PNEC values****DNEL values (worker)**

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	pentafluoroethane			354-33-6 206-557-8	
	inhalative	Long term (chronic)	systemic	16444	mg/m ³
2	difluoromethane			75-10-5 200-839-4	
	inhalative	Long term (chronic)	systemic	7035	mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	pentafluoroethane			354-33-6 206-557-8	
	inhalative	Long term (chronic)	systemic	1753	mg/m ³
2	difluoromethane			75-10-5 200-839-4	
	inhalative	Long term (chronic)	systemic	750	mg/m ³

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	pentafluoroethane		354-33-6 206-557-8	
	water	fresh water	0.1	mg/L

Trade name: R410A

Product no.: R410A

Current version : 3.0.0, issued: 11.01.2022

Replaced version: 2.0.0, issued: 29.03.2021

Region: GB

	water	fresh water sediment	0.6	mg/kg dry weight
	water	Aqua intermittent	1	mg/L
2	difluoromethane		75-10-5 200-839-4	
	water	fresh water	0.142	mg/L
	water	Aqua intermittent	1.42	mg/L
	water	fresh water sediment	0.543	mg/kg dry weight

8.2 Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, local exhaust at the work station if necessary. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

Self-contained breathing apparatus. In case of insufficient ventilation or long-term effect use breathing apparatus. Danger of suffocation due to high concentrations in breathing air.

Respiratory filter (gas) : AX

Eye / face protection

Tightly fitting safety glasses (EN 166).

Hand protection

Low-temperature-resistant gloves (EN 511). Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material Leather

Other

Chemical-resistant work clothes. Protective shoes.

Environmental exposure controls

Information regarding waste disposal, see chapter 13.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation	
gas	
Form/Colour	
liquified gas	
colourless	
Odour	
slightly like ether	
pH value	
Comments	neutral
Boiling point / boiling range	
Value	-51.4 °C
Reference pressure	1013 hPa
Melting point/freezing point	
No data available	
Decomposition temperature	

Trade name: R410A

Product no.: R410A

Current version : 3.0.0, issued: 11.01.2022

Replaced version: 2.0.0, issued: 29.03.2021

Region: GB

No data available			
Flash point			
No data available			
Ignition temperature			
No data available			
Flammability			
No data available			
Lower explosion limit			
none			
Reference substance		mixture R410A	
Source		supplier	
Upper explosion limit			
none			
Reference substance		mixture R410A	
Source		supplier	
Vapour pressure			
Value		16574	hPa
Reference temperature		25	°C
Value		30520	hPa
Reference temperature		50	°C
Relative vapour density			
Value		3	
Comments		Air = 1	
Evaporation rate			
Value		> 1	
Comments		CCl4 = 1	
Relative density			
No data available			
Density			
Value		1.062	g/cm³
Reference temperature		25	°C
Comments		as liquid	
Solubility in water			
Value		1.5	g/l
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	pentafluoroethane	354-33-6	206-557-8
log Pow		1.48	
Reference temperature		25	°C
with reference to		pH 6.34	
Method		OECD 107	
Source		ECHA	
2	difluoromethane	75-10-5	200-839-4
log Pow		0.21	
Reference temperature		25	°C
with reference to		pH 6,1	
Method		OECD 107	
Source		ECHA	

Trade name: R410A

Product no.: R410A

Current version : 3.0.0, issued: 11.01.2022

Replaced version: 2.0.0, issued: 29.03.2021

Region: GB

Viscosity

No data available

Particle characteristics**9.2 Other information****Other information**

No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

Dangerous reactions are not expected if the product is handled according to its intended use. For the avoidance of thermal reaction does not overheat.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Stable under recommended storage and handling conditions (See section 7).

10.4 Conditions to avoid

Temperatures > 50°C. Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Alkali metals; Earth alkali metals; Metal as powder; powdered metal salts

10.6 Hazardous decomposition products

None, if handled according to intended use. In case of fire: see section 5.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity**

No data available

Acute dermal toxicity

No data available

Acute inhalational toxicity

No	Substance name	CAS no.	EC no.
1	pentafluoroethane	354-33-6	206-557-8
ATE	>	800000	ppmV
Duration of exposure		4	h
State of aggregation	Gas		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Skin corrosion/irritation

No data available

Serious eye damage/irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No	Substance name	CAS no.	EC no.
1	pentafluoroethane	354-33-6	206-557-8
Type of examination	in vitro gene mutation study in bacteria		

Trade name: R410A

Product no.: R410A

Current version : 3.0.0, issued: 11.01.2022

Replaced version: 2.0.0, issued: 29.03.2021

Region: GB

Species	Salmonella typhimurium / Escherichia coli
Method	OECD 471
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
Type of examination	In vitro Mammalian Chromosomal Aberration Test
Species	Chinese hamster Ovary (CHO)
Method	OECD 473
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
Route of exposure	inhalational
Type of examination	Mammalian Erythrocyte Micronucleus Test, In vivo
Species	mouse
Method	OECD 474
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
2	difluoromethane
	75-10-5
	200-839-4
Type of examination	in vitro gene mutation study in bacteria
Species	Salmonella typhimurium / Escherichia coli
Method	OECD 471
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
Type of examination	In vitro Mammalian Chromosomal Aberration Test
Species	Human Lymphocyte
Method	OECD 473
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Reproduction toxicity

No data available

Carcinogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No	Substance name	CAS no.	EC no.
1	pentafluoroethane	354-33-6	206-557-8
Route of exposure	inhalational		
Species	rat		
Method	OECD 413		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	difluoromethane	75-10-5	200-839-4
Route of exposure	inhalational		
Species	rat		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Aspiration hazard

No data available

11.2 Information on other hazards**Endocrine disrupting properties**

No data available.

Other information

No data available.

SECTION 12: Ecological information

Trade name: R410A

Product no.: R410A

Current version : 3.0.0, issued: 11.01.2022

Replaced version: 2.0.0, issued: 29.03.2021

Region: GB

12.1 Toxicity

Toxicity to fish (acute)
No data available
Toxicity to fish (chronic)
No data available
Toxicity to Daphnia (acute)
No data available
Toxicity to Daphnia (chronic)
No data available
Toxicity to algae (acute)
No data available
Toxicity to algae (chronic)
No data available
Bacteria toxicity
No data available

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	pentafluoroethane	354-33-6	206-557-8
Type	aerobic biodegradation		
Value	appr.	5	%
Duration		28	d
Method	Closed Bottle Test (OECD 301D)		
Source	ECHA		
Evaluation	not readily biodegradable		
2	difluoromethane	75-10-5	200-839-4
Type	aerobic biodegradation		
Value		5	%
Duration		28	d
Method	OECD 301 D		
Source	ECHA		
Evaluation	not readily biodegradable		

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	pentafluoroethane	354-33-6	206-557-8
log Pow		1.48	
Reference temperature		25	°C
with reference to	pH 6.34		
Method	OECD 107		
Source	ECHA		
2	difluoromethane	75-10-5	200-839-4
log Pow		0.21	
Reference temperature		25	°C
with reference to	pH 6,1		
Method	OECD 107		
Source	ECHA		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment

Trade name: R410A**Product no.:** R410A**Current version :** 3.0.0, issued: 11.01.2022**Replaced version:** 2.0.0, issued: 29.03.2021**Region:** GB

PBT assessment	The product is not considered to be a PBT.
vPvB assessment	The product is not considered to be a vPvB.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

Other adverse effects
Contains fluorinated greenhouse gases. Global Warming Potential (GWP): 2088

12.8 Other information

Other information
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

dispose of in accordance with local regulation.

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Compressed gas packaging under pressure. Do not open by force. Do not heat above 50°C. Dispose of compressed gas packagings only if completely discharged. Do not burn empty compressed gas packagings. Do not pierce, cut or weld uncleaned containers.

SECTION 14: Transport information**14.1 Transport ADR/RID/ADN**

Class	2
Classification code	2A
Hazard identification no.	20
UN number	UN3163
Proper shipping name	LIQUEFIED GAS, N.O.S.
Technical name	pentafluoroethane difluoromethane
Tunnel restriction code	C/E
Label	2.2 RID: (+13)

14.2 Transport IMDG

Class	2.2
UN number	UN3163
Proper shipping name	LIQUEFIED GAS, N.O.S.
Technical name	pentafluoroethane difluoromethane
EmS	F-C, S-V
Label	2.2

14.3 Transport ICAO-TI / IATA

Class	2.2
UN number	UN3163
Proper shipping name	Liquefied gas, n.o.s.
Technical name	pentafluoroethane difluoromethane
Label	2.2

14.4 Other information

No data available.

14.5 Environmental hazards

Trade name: R410A

Product no.: R410A

Current version : 3.0.0, issued: 11.01.2022

Replaced version: 2.0.0, issued: 29.03.2021

Region: GB

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

To be transported always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of conduct in case of incident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances subject to restriction as listed in Annex XVII of the REACH regulation (EC) 1907/2006.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

Other regulations

REGULATION (EU) No 517/2014 on fluorinated greenhouse gases

Adhere to the national sanitary and occupational safety regulations when using this product.

15.2 Chemical safety assessment

Chemical safety assessments have been conducted for the substances in this mixture. For a mixture a chemical safety assessment according to (EC) 1907/2006 is not mandatory.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H220 Extremely flammable gas.

Creation of the safety data sheet

UMCO GmbH

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Trade name: R410A

Product no.: R410A

Current version : 3.0.0, issued: 11.01.2022

Replaced version: 2.0.0, issued: 29.03.2021

Region: GB

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 755619