according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Freon™ MO49 Plus (R-437A) Refrigerant

SDS-Identcode : 130000033955

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Refrigerant

stance/Mixture

Recommended restrictions

on use

For professional and industrial installation and use only.

1.3 Details of the supplier of the safety data sheet

Company : Chemours Netherlands B.V.

Baanhoekweg 22

3313 LA Dordrecht Netherlands

Telephone : +31-(0)-78-630-1011

Telefax : +31-78-6163737

E-mail address of person

responsible for the SDS

: sds-support@chemours.com

### 1.4 Emergency telephone number

+(353)-19014670 (CHEMTREC - Recommended); +353-(01) 809 2166 (Poison Information

Center of Ireland)

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Gases under pressure, Liquefied gas H280: Contains gas under pressure; may explode if

heated.

### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

Hazard pictograms :

 $\Diamond$ 

Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.

Precautionary statements : Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated

place.

#### Additional Labelling

Contains fluorinated greenhouse gases. (HFC-134a, HFC-125)

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

May displace oxygen and cause rapid suffocation.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
1,1,1,2-Tetrafluoroethane#	811-97-2 212-377-0 01-2119459374-33	Press. Gas Liquefied gas; H280	78.5
Pentafluoroethane#	354-33-6 206-557-8 01-2119485636-25	Press. Gas Liquefied gas; H280	19.5

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.10.2022	
9.0	21.04.2023	1333387-00048	Date of first issue: 27.02.2017	

Butane	106-97-8 203-448-7 601-004-00-0	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280 STOT SE 3; H336	1.4
Pentane	109-66-0 203-692-4 601-006-00-1	Flam. Liq. 2; H225 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	0.6

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : No special precautions are necessary for first aid responders.

If inhaled : If inhaled, remove to fresh air.

If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

In case of skin contact : Thaw frosted parts with lukewarm water. Do not rub affected

area.

Get medical attention immediately.

In case of eye contact : Get medical attention immediately.

If swallowed : Ingestion is not considered a potential route of exposure.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : May cause cardiac arrhythmia.

Other symptoms potentially related to misuse or inhalation

abuse are

Cardiac sensitisation Anaesthetic effects Light-headedness

Dizziness confusion

Lack of coordination

Drowsiness Unconsciousness

<sup>#</sup> Voluntarily-disclosed substance

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

Risks : Gas reduces oxygen available for breathing.

Contact with liquid or refrigerated gas can cause cold burns

and frostbite.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Because of possible disturbances of cardiac rhythm, cate-

cholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with spe-

cial caution.

**SECTION 5: Firefighting measures** 

5.1 Extinguishing media

Suitable extinguishing media : Not applicable

Will not burn

Unsuitable extinguishing

media

Not applicable Will not burn

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod: :

ucts

Hydrogen fluoride carbonyl fluoride Carbon oxides Fluorine compounds

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary. Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Fight fire remotely due to the risk of explosion. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

**SECTION 6: Accidental release measures** 

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Avoid skin contact with leaking liquid (danger of frostbite).

Ventilate the area.

Follow safe handling advice (see section 7) and personal pro-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

tective equipment recommendations (see section 8).

### 6.2 Environmental precautions

Environmental precautions :

Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ventilate the area.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Technical measures : Use equipment rated for cylinder pressure. Use a backflow

preventative device in piping. Close valve after each use and

when empty.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid breathing gas.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Wear cold insulating gloves/ face shield/ eye protection. Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet

piped to use point.

Prevent backflow into the gas tank.

Use a check valve or trap in the discharge line to prevent haz-

ardous back flow into the cylinder.

Use a pressure reducing regulator when connecting cylinder

to lower pressure (<3000 psig) piping or systems.

Close valve after each use and when empty. Do NOT change

or force fit connections.

Prevent the intrusion of water into the gas tank.

Never attempt to lift cylinder by its cap. Do not drag, slide or roll cylinders.

Use a suitable hand truck for cylinder movement. Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contami-

nated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Separate full containers from empty containers. Do not store near combustible materials. Avoid area where salt or other corrosive materials are present. Keep in properly labelled containers. Keep in a cool, well-ventilated place. Keep away from direct sunlight. Store in

accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:

Self-reactive substances and mixtures

Organic peroxides Oxidizing agents Flammable liquids Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures, which in contact with water, emit

flammable gases Explosives

Very acutely toxic substances and mixtures Acutely toxic substances and mixtures Substances and mixtures with chronic toxicity

Storage period : > 10 yr

Recommended storage tem-

perature

< 52 °C

Further information on stor-

age stability

The product has an indefinite shelf life when stored properly.

7.3 Specific end use(s)

Specific use(s) : No data available

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

Butane	106-97-8	OELV - 15 min (STEL)	1,000 ppm	IE OEL	
Pentane	109-66-0	TWA	1,000 ppm 3,000 mg/m3	2006/15/EC	
	Further infor	Further information: Indicative			
		OELV - 8 hrs (TWA)	1,000 ppm	IE OEL	

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
1,1,1,2- Tetrafluoroethane	Workers	Inhalation	Long-term systemic effects	13936 mg/m3
	Consumers	Inhalation	Long-term systemic effects	2476 mg/m3
Pentafluoroethane	Workers	Inhalation	Long-term systemic effects	16444 mg/m3
	Consumers	Inhalation	Long-term systemic effects	1753 mg/m3
Pentane	Workers	Inhalation	Long-term systemic effects	3000 mg/m3
	Workers	Skin contact	Long-term systemic effects	432 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	643 mg/m3
	Consumers	Skin contact	Long-term systemic effects	214 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	214 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
1,1,1,2-Tetrafluoroethane	Fresh water	0.1 mg/l
	Marine water	0.01 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	0.75 mg/kg dry
		weight (d.w.)
	Sewage treatment plant	73 mg/l
Pentafluoroethane	Fresh water	0.1 mg/l
	Freshwater - intermittent	1 mg/l
	Fresh water sediment	0.6 mg/kg dry
		weight (d.w.)
Pentane	Fresh water	0.23 mg/l
	Marine water	0.23 mg/l
	Intermittent use/release	0.88 mg/l
	Sewage treatment plant	3.6 mg/l
	Fresh water sediment	1.2 mg/kg dry
		weight (d.w.)
	Marine sediment	1.2 mg/kg dry
		weight (d.w.)
	Soil	0.55 mg/kg dry

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

weight (d.w.)

### 8.2 Exposure controls

### **Engineering measures**

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:

Chemical resistant goggles must be worn.

Face-shield

Equipment should conform to I.S. EN 166

Hand protection

Material : Low temperature resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change

gloves often!

Skin and body protection : Skin should be washed after contact.

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection. Equipment should conform to I.S. EN 14387

Filter type : Organic gas and low boiling vapour type (AX)

Protective measures : Wear cold insulating gloves/ face shield/ eye protection.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state : Liquefied gas

Colour : colourless, clear

Odour : slight, ether-like

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling : -32.3 °C

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

range

Flammability (solid, gas) : Will not burn

Upper explosion limit / Upper

flammability limit

Upper flammability limit Method: ASTM E681

None.

Lower explosion limit / Lower

flammability limit

Lower flammability limit

Method: ASTM E681

None.

Flash point : Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : No data available

Viscosity

Viscosity, kinematic : Not applicable

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

: Not applicable

Vapour pressure : 7,949 hPa (25 °C)

Relative density : 1.18 (25 °C)

Density : 1.192 g/cm³ (21 °C)

(as liquid)

Relative vapour density : 3.7

Particle characteristics

Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Not classified as a reactivity hazard.

#### 10.2 Chemical stability

Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

#### 10.4 Conditions to avoid

Conditions to avoid : This substance is not flammable in air at temperatures up to

100 °C (212 °F) at atmospheric pressure. However, mixtures of this substance with high concentrations of air at elevated pressure and/or temperature can become combustible in the presence of an ignition source. This substance can also become combustible in an oxygen enriched environment (oxygen concentrations greater than that in air). Whether a mixture containing this substance and air, or this substance in an oxygen enriched atmosphere become combustible depends on the inter-relationship of 1) the temperature 2) the pressure, and 3) the proportion of oxygen in the mixture. In general, this substance should not be allowed to exist with air above atmospheric pressure or at high temperatures; or in an oxygen enriched environment. For example this substance should NOT be mixed with air under pressure for leak testing or other

purposes.

Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

#### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of : Inhalation exposure Skin contact

Eye contact

### **Acute toxicity**

Not classified based on available information.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

### **Components:**

#### 1,1,1,2-Tetrafluoroethane:

Acute oral toxicity : Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 567000 ppm

Exposure time: 4 h
Test atmosphere: gas

Method: OECD Test Guideline 403

No observed adverse effect concentration (Dog): 40000 ppm

Test atmosphere: gas

Remarks: Cardiac sensitisation

Lowest observed adverse effect concentration (Dog): 80000

ppm

Test atmosphere: gas

Symptoms: May cause cardiac arrhythmia.

Cardiac sensitisation threshold limit (Dog): 334,000 mg/m3

Test atmosphere: gas

Symptoms: May cause cardiac arrhythmia.

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal

toxicity

Pentafluoroethane:

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm

Exposure time: 4 h Test atmosphere: gas

Method: OECD Test Guideline 403

No observed adverse effect concentration (Dog): 75000 ppm

Remarks: Cardiac sensitisation

Cardiac sensitisation threshold limit (Dog): 368.159 mg/m3

Remarks: Cardiac sensitisation

**Butane:** 

Acute inhalation toxicity : LC50 (Rat): 570000 ppm

Exposure time: 15 min Test atmosphere: gas

Remarks: Based on data from similar materials

Pentane:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icity

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

Remarks: Based on data from similar materials

#### Skin corrosion/irritation

Not classified based on available information.

### **Components:**

### 1,1,1,2-Tetrafluoroethane:

Result : No skin irritation

Pentane:

Species : Rabbit

Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

### Serious eye damage/eye irritation

Not classified based on available information.

### Components:

### 1,1,1,2-Tetrafluoroethane:

Result : No eye irritation

Pentane:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

### **Components:**

#### 1,1,1,2-Tetrafluoroethane:

Exposure routes : Skin contact Result : negative

Exposure routes : Inhalation Species : Rat Result : negative

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

Exposure routes : Inhalation
Species : Humans
Result : negative

Pentane:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

### Germ cell mutagenicity

Not classified based on available information.

#### Components:

#### 1,1,1,2-Tetrafluoroethane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: inhalation (gas) Method: OECD Test Guideline 474

Result: negative

Test Type: Unscheduled DNA synthesis (UDS) test with

mammalian liver cells in vivo

Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 486

Result: negative

Germ cell mutagenicity- As-

sessment

Weight of evidence does not support classification as a germ

cell mutagen.

#### Pentafluoroethane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 18.10.2022 21.04.2023 1333387-00048 Date of first issue: 27.02.2017 9.0

Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo Test Type: Mammalian erythrocyte micronucleus test (in vivo

> cytogenetic assay) Species: Mouse

Application Route: inhalation (gas) Method: OECD Test Guideline 474

Result: negative

**Butane:** 

Genotoxicity in vitro Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo Test Type: Mammalian erythrocyte micronucleus test (in vivo

> cytogenetic assay) Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Pentane:

Test Type: Chromosome aberration test in vitro Genotoxicity in vitro

Method: Directive 67/548/EEC, Annex V, B.10.

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo Test Type: Mammalian erythrocyte micronucleus test (in vivo

> cytogenetic assay) Species: Rat

Application Route: inhalation (vapour)

Method: Directive 67/548/EEC, Annex V, B.12.

Result: negative

#### Carcinogenicity

Not classified based on available information.

#### **Components:**

### 1,1,1,2-Tetrafluoroethane:

**Species** : Rat

Application Route : inhalation (gas)

Exposure time 2 Years

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

Method : OECD Test Guideline 453

Result : negative

Carcinogenicity - Assess-

ment

: Weight of evidence does not support classification as a car-

cinogen

### Reproductive toxicity

Not classified based on available information.

#### **Components:**

### 1,1,1,2-Tetrafluoroethane:

Effects on fertility : Species: Mouse

Application Route: Inhalation

Result: negative

Effects on foetal develop-

ment

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rabbit

Application Route: inhalation (gas) Method: OECD Test Guideline 414

Result: negative

Reproductive toxicity - As-

sessment

: Weight of evidence does not support classification for repro-

ductive toxicity

### Pentafluoroethane:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 414

Result: negative

#### **Butane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 422

Result: negative

Effects on foetal develop-

ment

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: inhalation (gas)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

Method: OECD Test Guideline 422

Result: negative

Pentane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

: Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

### STOT - single exposure

Not classified based on available information.

### **Components:**

### 1,1,1,2-Tetrafluoroethane:

Exposure routes : inhalation (gas)

Assessment : No significant health effects observed in animals at concentra-

tions of 20000 ppmV/4h or less

**Butane:** 

Assessment : May cause drowsiness or dizziness.

Remarks : Based on data from similar materials

Pentane:

Assessment : May cause drowsiness or dizziness.

### STOT - repeated exposure

Not classified based on available information.

### **Components:**

### 1,1,1,2-Tetrafluoroethane:

Exposure routes : inhalation (gas)

Assessment : No significant health effects observed in animals at concentra-

tions of 250 ppmV/6h/d or less.

### Repeated dose toxicity

### **Components:**

### 1,1,1,2-Tetrafluoroethane:

Species : Rat, male and female

NOAEL : 50000 ppm

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

LOAEL : >50000 ppm Application Route : inhalation (gas)

Exposure time : 2 yr

Method : OECD Test Guideline 453

Pentafluoroethane:

Species : Rat

NOAEL : >= 50000 ppm
Application Route : inhalation (gas)
Exposure time : 13 Weeks

Method : OECD Test Guideline 413

**Butane:** 

Species : Rat

NOAEL : >= 9000 ppm
Application Route : inhalation (gas)
Exposure time : 6 Weeks

Method : OECD Test Guideline 422

Pentane:

Species : Rat

NOAEL : > 6700 ppm

Application Route : inhalation (gas)

Exposure time : 13 Weeks

Method : OECD Test Guideline 413

### **Aspiration toxicity**

Not classified based on available information.

### Components:

### 1,1,1,2-Tetrafluoroethane:

No aspiration toxicity classification

#### Pentane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

### 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

### **SECTION 12: Ecological information**

### 12.1 Toxicity

#### **Components:**

### 1,1,1,2-Tetrafluoroethane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 450 mg/l

Exposure time: 96 h

Method: Regulation (EC) No. 440/2008, Annex, C.1

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 980 mg/l

Exposure time: 48 h

Method: Regulation (EC) No. 440/2008, Annex, C.2

Toxicity to algae/aquatic

plants

ErC50 (green algae): > 100 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Pentafluoroethane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): > 1

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Pentane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.26 mg/l

Exposure time: 96 h

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 2.7 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

ErC50 (Scenedesmus capricornutum (fresh water algae)):

10.7 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

NOEC (Scenedesmus capricornutum (fresh water algae)):

2.04 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

**Ecotoxicology Assessment** 

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Remarks: Based on national or regional regulation.

12.2 Persistence and degradability

**Components:** 

1,1,1,2-Tetrafluoroethane:

Biodegradability : Result: Not readily biodegradable.

Method: OECD Test Guideline 301D

Pentafluoroethane:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301D

**Butane:** 

Biodegradability : Result: Readily biodegradable.

Remarks: Based on data from similar materials

Pentane:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 87 % Exposure time: 28 d

12.3 Bioaccumulative potential

**Components:** 

1,1,1,2-Tetrafluoroethane:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

: log Pow: 1.06

Pentafluoroethane:

Partition coefficient: n- : Pow: 1.48

octanol/water Method: OECD Test Guideline 107

**Butane:** 

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

Partition coefficient: n-

octanol/water

: log Pow: 2.89

Pentane:

Partition coefficient: n-

octanol/water

log Pow: 3.45

### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

#### 12.6 Endocrine disrupting properties

### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

### Global warming potential

Regulation (EU) No 517/2014 on fluorinated greenhouse gases

#### **Product:**

100-year global warming potential: 1,805

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Empty pressure vessels should be returned to the supplier. If not otherwise specified: Dispose of as unused product.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADN : UN 1078
ADR : UN 1078
RID : UN 1078
IMDG : UN 1078
IATA : UN 1078

14.2 UN proper shipping name

**ADN** : REFRIGERANT GAS, N.O.S.

(1,1,1,2-Tetrafluoroethane, Pentafluoroethane)

**ADR** : REFRIGERANT GAS, N.O.S.

(1,1,1,2-Tetrafluoroethane, Pentafluoroethane)

RID : REFRIGERANT GAS, N.O.S.

(1,1,1,2-Tetrafluoroethane, Pentafluoroethane)

**IMDG** : REFRIGERANT GAS, N.O.S.

(1,1,1,2-Tetrafluoroethane, Pentafluoroethane)

IATA : Refrigerant gas, n.o.s.

(1,1,1,2-Tetrafluoroethane, Pentafluoroethane)

### 14.3 Transport hazard class(es)

Class Subsidiary risks

ADN : 2 2.2 ADR : 2 2.2

**RID** : 2 2.2, (13)

IMDG : 2.2 IATA : 2.2

### 14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 2A Hazard Identification Number : 20 Labels : 2.2

**ADR** 

Packing group : Not assigned by regulation

Classification Code : 2A
Hazard Identification Number : 20
Labels : 2.2
Tunnel restriction code : (C/E)

**RID** 

Packing group : Not assigned by regulation

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 18.10.2022 21.04.2023 1333387-00048 Date of first issue: 27.02.2017 9.0

Classification Code 2A Hazard Identification Number 20 Labels 2.2 ((13))

**IMDG** 

Packing group Not assigned by regulation

Labels 2.2 F-C, S-V EmS Code

IATA (Cargo)

Packing instruction (cargo 200

aircraft)

Packing group Not assigned by regulation Non-flammable, non-toxic Gas Labels

IATA (Passenger)

Packing instruction (passen-200

ger aircraft)

Not assigned by regulation Packing group Labels Non-flammable, non-toxic Gas

14.5 Environmental hazards

ADN

Environmentally hazardous no

Environmentally hazardous no

Environmentally hazardous no

**IMDG** 

Marine pollutant no

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mix-

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: Number on list 75

If you intend to use this product as tattoo ink, please contact your vendor.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

#### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

Other information : Freon™ and any associated logos are trademarks or copy-

rights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The

Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or

nominated distributors.

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical

lines.

#### **Full text of H-Statements**

H220 : Extremely flammable gas.

H225 : Highly flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H304 : May be fatal if swallowed and enters airways.

H336 : May cause drowsiness or dizziness.

H411 : Toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Flam. Gas : Flammable gases Flam. Liq. : Flammable liquids

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

Press. Gas : Gases under pressure

STOT SE : Specific target organ toxicity - single exposure

2006/15/EC : Europe. Indicative occupational exposure limit values

IE OEL : Ireland. List of Chemical Agents and Occupational Exposure

Limit Values - Schedule 1

2006/15/EC / TWA : Limit Value - eight hours

IE OEL / OELV - 8 hrs (TWA) : Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min : Occupational exposure limit value (15-minute reference peri-

(STEL) od)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level: NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

Sheet

Sources of key data used to compile the Safety Data

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

### Classification of the mixture:

### Classification procedure:

Press. Gas Liquefied gas H280 Based on product data or assessment

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## Freon™ MO49 Plus (R-437A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 18.10.2022

 9.0
 21.04.2023
 1333387-00048
 Date of first issue: 27.02.2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

IE / EN