

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version 6.5 Revision Date: 26.02.2020 SDS Number: 1324819-00036 Date of last issue: 27.09.2019
Date of first issue: 27.02.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Freon™ MO59 (R-417A) Refrigerant
SDS-Identcode : 130000000132

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Refrigerant
Recommended restrictions on use : For professional and industrial installation and use only.

1.3 Details of the supplier of the safety data sheet

Company : Chemours Netherlands B.V.
Baanhoekweg 22
3313 LA Dordrecht Netherlands
Telephone : +31-(0)-78-630-1011
Telefax : +31-78-6163737
E-mail address of person responsible for the SDS : sds-support@chemours.com

1.4 Emergency telephone number

+(44)-870-8200418 (CHEMTREC - Recommended)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Gases under pressure, Liquefied gas H280: Contains gas under pressure; may explode if heated.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version 6.5 Revision Date: 26.02.2020 SDS Number: 1324819-00036 Date of last issue: 27.09.2019
Date of first issue: 27.02.2017

Precautionary statements : **Storage:**
P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Additional Labelling

Contains fluorinated greenhouse gases. (HFC-134a, HFC-125)

2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT). This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

May displace oxygen and cause rapid suffocation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
1,1,1,2-Tetrafluoroethane*	811-97-2 212-377-0 01-2119459374-33	Press. Gas Liquefied gas; H280	50
Pentafluoroethane*	354-33-6 206-557-8 01-2119485636-25	Press. Gas Liquefied gas; H280	46.6
Butane	106-97-8 203-448-7 601-004-00-0	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280 STOT SE 3; H336	3.4

* Voluntarily-disclosed non-hazardous substance
For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 27.09.2019
6.5	26.02.2020	1324819-00036	Date of first issue: 27.02.2017

- Protection of first-aiders : No special precautions are necessary for first aid responders.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : Thaw frosted parts with lukewarm water. Do not rub affected area.
Get medical attention immediately.
- In case of eye contact : Get medical attention immediately.
- If swallowed : Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : May cause cardiac arrhythmia.
- Other symptoms potentially related to misuse or inhalation abuse are
Cardiac sensitisation
Anaesthetic effects
Light-headedness
Dizziness
confusion
Lack of coordination
Drowsiness
Unconsciousness
- Risks : Contact with liquid or refrigerated gas can cause cold burns and frostbite.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with special caution.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Not applicable
Will not burn
- Unsuitable extinguishing media : Not applicable
Will not burn

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion prod- : Hydrogen fluoride

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 27.09.2019
6.5	26.02.2020	1324819-00036	Date of first issue: 27.02.2017

ucts	carbonyl fluoride Carbon oxides Fluorine compounds
------	--

5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Fight fire remotely due to the risk of explosion. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
-

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Evacuate personnel to safe areas. Avoid skin contact with leaking liquid (danger of frostbite). Ventilate the area. Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

- Environmental precautions : Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Ventilate the area. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Technical measures : Use equipment rated for cylinder pressure. Use a backflow preventative device in piping. Close valve after each use and when empty.
- Local/Total ventilation : Use only with adequate ventilation.
-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 27.09.2019
6.5	26.02.2020	1324819-00036	Date of first issue: 27.02.2017

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment

Wear cold insulating gloves/ face shield/ eye protection.
Prevent backflow into the gas tank.
Open the valves slowly to prevent pressure surges.
Close valve after each use and when empty. Do NOT change or force fit connections.
Prevent the intrusion of water into the gas tank.
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Avoid breathing gas.
Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point.
Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.
Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems.
Never attempt to lift cylinder by its cap.
Do not drag, slide or roll cylinders.
Use a suitable hand truck for cylinder movement.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Separate full containers from empty containers. Do not store near combustible materials. Avoid area where salt or other corrosive materials are present. Keep in properly labelled containers. Keep in a cool, well-ventilated place. Keep away from direct sunlight. Store in accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:

- Self-reactive substances and mixtures
- Organic peroxides
- Oxidizing agents
- Flammable liquids
- Flammable solids
- Pyrophoric liquids
- Pyrophoric solids
- Self-heating substances and mixtures
- Substances and mixtures, which in contact with water, emit flammable gases
- Explosives

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version 6.5 Revision Date: 26.02.2020 SDS Number: 1324819-00036 Date of last issue: 27.09.2019
Date of first issue: 27.02.2017

Acutely toxic substances and mixtures
Substances and mixtures with chronic toxicity

Storage period : > 10 yr

Recommended storage temperature : < 52 °C

Further information on storage stability : The product has an indefinite shelf life when stored properly.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
1,1,1,2-Tetrafluoroethane	811-97-2	TWA	1,000 ppm 4,240 mg/m ³	GB EH40
Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.				
Butane	106-97-8	STEL	750 ppm 1,810 mg/m ³	GB EH40
		TWA	600 ppm 1,450 mg/m ³	GB EH40

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
1,1,1,2-Tetrafluoroethane	Workers	Inhalation	Long-term systemic effects	13936 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	2476 mg/m ³
Pentafluoroethane	Workers	Inhalation	Long-term systemic effects	16444 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	1753 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
1,1,1,2-Tetrafluoroethane	Fresh water	0.1 mg/l
	Marine water	0.01 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	0.75 mg/kg dry weight (d.w.)
	Sewage treatment plant	73 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version 6.5 Revision Date: 26.02.2020 SDS Number: 1324819-00036 Date of last issue: 27.09.2019
Date of first issue: 27.02.2017

Pentafluoroethane	Fresh water	0.1 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	0.6 mg/kg

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
Face-shield
Equipment should conform to BS EN 166

Hand protection
Material : Heat resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Skin and body protection : Skin should be washed after contact.

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to BS EN 14387

Filter type : Organic gas and low boiling vapour type (AX)

Protective measures : Wear cold insulating gloves/ face shield/ eye protection.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Liquefied gas

Colour : colourless

Odour : slight, ether-like

Odour Threshold : No data available

pH : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 27.09.2019
6.5	26.02.2020	1324819-00036	Date of first issue: 27.02.2017

Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	-39.1 °C
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Will not burn
Upper explosion limit / Upper flammability limit	:	Upper flammability limit Method: ASTM E681 None.
Lower explosion limit / Lower flammability limit	:	Lower flammability limit Method: ASTM E681 None.
Vapour pressure	:	9,835 hPa (25 °C)
Relative vapour density	:	3.8 (Air = 1.0)
Relative density	:	1.15 (25 °C)
Density	:	1.2 g/cm ³ (20 °C) (as liquid)
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size	:	Not applicable
---------------	---	----------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 27.09.2019
6.5	26.02.2020	1324819-00036	Date of first issue: 27.02.2017

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : This substance is not flammable in air at temperatures up to 100 °C (212 °F) at atmospheric pressure. However, mixtures of this substance with high concentrations of air at elevated pressure and/or temperature can become combustible in the presence of an ignition source. This substance can also become combustible in an oxygen enriched environment (oxygen concentrations greater than that in air). Whether a mixture containing this substance and air, or this substance in an oxygen enriched atmosphere become combustible depends on the inter-relationship of 1) the temperature 2) the pressure, and 3) the proportion of oxygen in the mixture. In general, this substance should not be allowed to exist with air above atmospheric pressure or at high temperatures; or in an oxygen enriched environment. For example this substance should NOT be mixed with air under pressure for leak testing or other purposes.
Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Eye contact

Acute toxicity

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 27.09.2019
6.5	26.02.2020	1324819-00036	Date of first issue: 27.02.2017

Acute inhalation toxicity : LC50 (Rat): > 567000 ppm
Exposure time: 4 h
Test atmosphere: gas

No observed adverse effect concentration (Dog): 40000 ppm
Test atmosphere: gas
Symptoms: Cardiac sensitisation

Lowest observed adverse effect concentration (Dog): 80000 ppm
Test atmosphere: gas
Symptoms: Cardiac sensitisation

Cardiac sensitisation threshold limit (Dog): 334,000 mg/m³
Test atmosphere: gas
Symptoms: Cardiac sensitisation

Pentafluoroethane:

Acute inhalation toxicity : LC0 (Rat): > 800000 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: OECD Test Guideline 403

Butane:

Acute inhalation toxicity : LC50 (Rat): 570000 ppm
Exposure time: 15 min
Test atmosphere: gas
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 27.09.2019
6.5	26.02.2020	1324819-00036	Date of first issue: 27.02.2017

Respiratory sensitisation

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Species : Rat
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Pentafluoroethane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Butane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version 6.5 Revision Date: 26.02.2020 SDS Number: 1324819-00036 Date of last issue: 27.09.2019
Date of first issue: 27.02.2017

Carcinogenicity

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

Reproductive toxicity

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

Pentafluoroethane:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 414
Result: negative

Butane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 422
Result: negative

STOT - single exposure

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version 6.5 Revision Date: 26.02.2020 SDS Number: 1324819-00036 Date of last issue: 27.09.2019
Date of first issue: 27.02.2017

Components:

Butane:

Assessment : May cause drowsiness or dizziness.
Remarks : Based on data from similar materials

STOT - repeated exposure

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Assessment : No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

Repeated dose toxicity

Components:

1,1,1,2-Tetrafluoroethane:

Species : Rat
NOAEL : 50000 ppm
LOAEL : > 50000 ppm
Application Route : inhalation (gas)
Exposure time : 90 d
Method : OECD Test Guideline 413
Remarks : No significant adverse effects were reported

Pentafluoroethane:

Species : Rat
NOAEL : \geq 50000 ppm
Application Route : inhalation (gas)
Exposure time : 13 Weeks
Method : OECD Test Guideline 413

Butane:

Species : Rat
NOAEL : \geq 9000 ppm
Application Route : inhalation (gas)
Exposure time : 6 Weeks
Method : OECD Test Guideline 422

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version 6.5 Revision Date: 26.02.2020 SDS Number: 1324819-00036 Date of last issue: 27.09.2019
Date of first issue: 27.02.2017

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,1,1,2-Tetrafluoroethane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 450 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 980 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (algae): 142 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 13.2 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

Pentafluoroethane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 450 mg/l
Exposure time: 96 h
Method: Directive 67/548/EEC, Annex V, C.1.
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 980 mg/l
Exposure time: 48 h
Method: Directive 67/548/EEC, Annex V, C.2.
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 114 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 13.2 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

1,1,1,2-Tetrafluoroethane:

Biodegradability : Result: Not readily biodegradable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 27.09.2019
6.5	26.02.2020	1324819-00036	Date of first issue: 27.02.2017

Pentafluoroethane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Butane:

Biodegradability : Result: Readily biodegradable.
Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

Components:

1,1,1,2-Tetrafluoroethane:

Partition coefficient: n-octanol/water : log Pow: 1.06

Pentafluoroethane:

Partition coefficient: n-octanol/water : Pow: 1.48 (25 °C)

Butane:

Partition coefficient: n-octanol/water : log Pow: 2.89

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).. This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB)..

12.6 Other adverse effects

Global warming potential

Regulation (EU) No 517/2014 on fluorinated greenhouse gases

Product:

100-year global warming potential: 2,346

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 27.09.2019
6.5	26.02.2020	1324819-00036	Date of first issue: 27.02.2017

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty pressure vessels should be returned to the supplier. If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

ADN	: UN 1078
ADR	: UN 1078
RID	: UN 1078
IMDG	: UN 1078
IATA	: UN 1078

14.2 UN proper shipping name

ADN	: REFRIGERANT GAS, N.O.S. (1,1,1,2-Tetrafluoroethane, Pentafluoroethane)
ADR	: REFRIGERANT GAS, N.O.S. (1,1,1,2-Tetrafluoroethane, Pentafluoroethane)
RID	: REFRIGERANT GAS, N.O.S. (1,1,1,2-Tetrafluoroethane, Pentafluoroethane)
IMDG	: REFRIGERANT GAS, N.O.S. (1,1,1,2-Tetrafluoroethane, Pentafluoroethane)
IATA	: Refrigerant gas, n.o.s. (1,1,1,2-Tetrafluoroethane, Pentafluoroethane)

14.3 Transport hazard class(es)

ADN	: 2
ADR	: 2
RID	: 2
IMDG	: 2.2
IATA	: 2.2

14.4 Packing group

ADN	
Packing group	: Not assigned by regulation
Classification Code	: 2A
Hazard Identification Number	: 20
Labels	: 2.2

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 27.09.2019
6.5	26.02.2020	1324819-00036	Date of first issue: 27.02.2017

ADR

Packing group : Not assigned by regulation
Classification Code : 2A
Hazard Identification Number : 20
Labels : 2.2
Tunnel restriction code : (C/E)

RID

Packing group : Not assigned by regulation
Classification Code : 2A
Hazard Identification Number : 20
Labels : 2.2 ((13))

IMDG

Packing group : Not assigned by regulation
Labels : 2.2
EmS Code : F-C, S-V

IATA (Cargo)

Packing instruction (cargo aircraft) : 200
Packing group : Not assigned by regulation
Labels : Non-flammable, non-toxic Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 200
Packing group : Not assigned by regulation
Labels : Non-flammable, non-toxic Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 27.09.2019
6.5	26.02.2020	1324819-00036	Date of first issue: 27.02.2017

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
18	Liquefied extremely flammable gases (including LPG) and natural gas	50 t	200 t

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Freon™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC. Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H220 : Extremely flammable gas.
H280 : Contains gas under pressure; may explode if heated.
H336 : May cause drowsiness or dizziness.

Full text of other abbreviations

Flam. Gas : Flammable gases
Press. Gas : Gases under pressure
STOT SE : Specific target organ toxicity - single exposure

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 27.09.2019
6.5	26.02.2020	1324819-00036	Date of first issue: 27.02.2017

GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Press. Gas Liquefied gas H280

Classification procedure:

Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Freon™ MO59 (R-417A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 27.09.2019
6.5	26.02.2020	1324819-00036	Date of first issue: 27.02.2017

intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN