

Trade name: R290- Propane 2.5; Tegan®290, Propane 2.5

Product no.: R290

Current version : 1.1.0, issued: 13.05.2020

Replaced version: 1.0.0, issued: 20.02.2019

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

R290- Propane 2.5; Tegan®290, Propane 2.5

Substance name propane
REACH registration no. 01-2119486944-21

Identification numbers

CAS no. 74-98-6
EC no. 200-827-9
Index no. 601-003-00-5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Industrial Use
Professional use
Formulation of mixtures

Fuel
Pure chemical
aerosol
propellant
Consumer use
Refrigerant

Uses advised against

No other use is recommended.

1.3 Details of the supplier of the safety data sheet

Address

TEGA - Technische Gase und Gasetechnik GmbH
Werner-von-Siemens-Straße 18
97076 Würzburg

Telephone no. +49 931 2093-220
Fax no. +49 931 2093-180
e-mail kaeltmittel@tega.de

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):
+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Flam. Gas 1; H220
Press. Gas liq.; H280

Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
U	-	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation

Trade name: R290- Propane 2.5; Tegan®290, Propane 2.5**Product no.:** R290**Current version :** 1.1.0, issued: 13.05.2020**Replaced version:** 1.0.0, issued: 20.02.2019**Region:** GB

(EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3 and 4 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Product identifier

74-98-6 (propane)

Hazard pictograms

GHS02



GHS04

Signal word

Danger

Hazard statement(s)

H220

Extremely flammable gas.

H280

Contains gas under pressure; may explode if heated.

Precautionary statement(s)

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P377

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381

In case of leakage, eliminate all ignition sources.

P403

Store in a well-ventilated place.

2.3 Other hazards

Contact with the liquid can cause cold burns or frostbite.

PBT assessment

The product is not considered to be a PBT.

vPvB assessment

The product is not considered to be a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical characterization

Substance name propane

Formula C₃H₈

Molecular weight 44.09

Identification numbers

CAS no. 74-98-6

EC no. 200-827-9

Index no. 601-003-00-5

3.2 Mixtures

Not applicable. The product is not a mixture.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove affected person from danger area, lay him down. Seek medical advice

Trade name: R290- Propane 2.5; Tegan®290, Propane 2.5**Product no.:** R290**Current version :** 1.1.0, issued: 13.05.2020**Replaced version:** 1.0.0, issued: 20.02.2019**Region:** GB

immediately.

After inhalation

Remove affected persons from dangerous area by observing suitable respiratory protection measures. Ensure supply of fresh air. Irregular breathing/no breathing: artificial respiration. Call a doctor immediately.

After skin contact

In case of contact with skin wash off immediately with soap and water. In case of frostbite, rinse with plenty of water. Do not remove clothing.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes).

After ingestion

Rinse mouth thoroughly with water. Do not induce vomiting. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed**Symptoms**

Shortness of breath; Frostbite; respiratory arrest. Unconsciousness

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Extinguishing powder; Water spray jet; Water mist; Foam

Unsuitable extinguishing media

High power water jet; Carbon dioxide

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide and carbon dioxide; May explode if exposed to heat. Liquefied gas: Spilled liquid can cause cold burns. This gas is heavier than air and may accumulate in low areas.

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear full protective suit. Containers close to fire should be transferred to a safe place. Cool closed containers exposed to fire with water. Pressure increase, bursting and explosion hazard during heating. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Ensure adequate ventilation. Keep away from ignition sources. Do not breathe gas. Cordon and mark contaminated area. Remove persons to safety. Risk of explosion.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Avoid release in the environment. Suppress gases/vapours/mists with water spray jet.

6.3 Methods and material for containment and cleaning up

Ensure adequate ventilation. Dispose of absorbed material in accordance with the regulations.

6.4 Reference to other sections

Information regarding safe handling, see chapter 7. Information regarding personal protective measures, see chapter 8. Information regarding waste disposal, see chapter 13.

Trade name: R290- Propane 2.5; Tegan®290, Propane 2.5**Product no.:** R290**Current version :** 1.1.0, issued: 13.05.2020**Replaced version:** 1.0.0, issued: 20.02.2019**Region:** GB**SECTION 7: Handling and storage****7.1 Precautions for safe handling****Advice on safe handling**

Only qualified and trained persons are authorised to handle. Provide good ventilation at the work area (local exhaust ventilation, if necessary). To be used only according to instructions for use. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose containers heat or sources of ignition. In case of accidental release: danger due to low temperature of the liquid product. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Comply with the health and safety at work laws.

General protective and hygiene measures

Wash hands before breaks and after work. Do not inhale gases. Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Have emergency shower available.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Isolate from sources of heat, sparks and open flame. Take precautionary measures against electrostatic loading (earthing necessary during loading operations). Use explosion-proof equipment/fittings and non-sparking tools. Electrical equipment should be protected to the appropriate standard.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Keep container tightly closed in a cool, well-ventilated place, open and handle carefully. Protect from heat and direct sunlight.

Recommended storage temperature

Value < 50 °C

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

Do not store together with: combustible materials; oxidizing agents; oxidizing substances; spontaneously combusting substances; explosive substances

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters**

No parameters available for monitoring.

8.2 Exposure controls**Appropriate engineering controls**

Ensure adequate ventilation, local exhaust at the work station if necessary. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment**Respiratory protection**

Self-contained breathing apparatus. In case of insufficient ventilation or long-term effect use breathing apparatus.
Respiratory filter (gas) : AX

Eye / face protection

Tightly fitting safety glasses (EN 166).

Hand protection

Low-temperature-resistant gloves (EN 511). Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility

Trade name: R290- Propane 2.5; Tegan®290, Propane 2.5**Product no.:** R290**Current version :** 1.1.0, issued: 13.05.2020**Replaced version:** 1.0.0, issued: 20.02.2019**Region:** GB

and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material Leather

Other

Chemical-resistant work clothes. Fire-resistant antistatic protective clothing. Protective shoes.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form/Colour	
liquified gas	
colourless	
Odour	
odourless	
Odour threshold	
No data available	
pH value	
No data available	
Boiling point / boiling range	
Value	-42.1 °C
Reference pressure	101.32 kPa
Melting point / melting range	
Value	-187.6 °C
Decomposition point / decomposition range	
Value	650 °C
Flash point	
No data available	
Auto-ignition temperature	
Value	472 °C
Oxidising properties	
No data available	
Explosive properties	
May form explosive gas-air mixtures.	
Flammability (solid, gas)	
highly flammable	
Lower flammability or explosive limits	
Value	1.7 % vol
Upper flammability or explosive limits	
Value	12.5 % vol
Vapour pressure	
Value	953.25 kPa
Reference temperature	25 °C
Vapour density	
Value	1.56
Reference temperature	0 °C

with 1907/2006/EC

Trade name: R290- Propane 2.5; Tegan®290, Propane 2.5

Product no.: R290

Current version : 1.1.0, issued: 13.05.2020

Replaced version: 1.0.0, issued: 20.02.2019

Region: GB

Comments	Air = 1
----------	---------

Evaporation rate

No data available

Relative density

Value	0.5853
Reference temperature	-45 °C

Density

No data available

Solubility in water

Value	75 mg/l
-------	---------

Solubility(ies)

No data available

Partition coefficient: n-octanol/water

No	Substance name	CAS no.	EC no.
1	propane	74-98-6	200-827-9
log Pow	appr.	1.8	
Method	QSAR		
Source	ECHA		

Viscosity

Value	0.08 mPa*s
Reference temperature	17.9 °C
Type	dynamic

9.2 Other information**Other information**

Critical Temp.: 96,7 °C

SECTION 10: Stability and reactivity**10.1 Reactivity**

Dangerous reactions are not expected if the product is handled according to its intended use.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

May ignite when exposed to strong oxydising agents. Risk of formation of explosive gas mixtures in air.

10.4 Conditions to avoid

T > 48 °C; Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Oxidizing agents; humidity

10.6 Hazardous decomposition products

None, if handled according to intended use.

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute oral toxicity**

No data available

Acute dermal toxicity

No data available

with 1907/2006/EC

Trade name: R290- Propane 2.5; Tegan®290, Propane 2.5

Product no.: R290

Current version : 1.1.0, issued: 13.05.2020

Replaced version: 1.0.0, issued: 20.02.2019

Region: GB

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	propane	74-98-6	200-827-9
LC50	>	800000	ppmV
Duration of exposure		0.25	h
State of aggregation	Gas		
Species	rat		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Skin corrosion/irritation	
No data available	

Serious eye damage/irritation	
No data available	

Respiratory or skin sensitisation	
No data available	

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	propane	74-98-6	200-827-9
Route of exposure	inhalational		
Species	Salmonella typhimurium		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	propane	74-98-6	200-827-9
Route of exposure	inhalational		
Species	rat		
Method	OECD 422		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Carcinogenicity	
No data available	

STOT - single exposure	
No data available	

STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	propane	74-98-6	200-827-9
Route of exposure	inhalational		
Species	rat		
Method	OECD 422		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Aspiration hazard	
No data available	

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)	
No data available	

Toxicity to fish (chronic)	

with 1907/2006/EC

Trade name: R290- Propane 2.5; Tegan®290, Propane 2.5

Product no.: R290

Current version : 1.1.0, issued: 13.05.2020

Replaced version: 1.0.0, issued: 20.02.2019

Region: GB

No data available

Toxicity to Daphnia (acute)

No data available

Toxicity to Daphnia (chronic)

No data available

Toxicity to algae (acute)

No data available

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	propane	74-98-6	200-827-9
Type		aerobic biodegradation	
Value		50	%
Duration		3	d
Method		QSAR	
Source		ECHA	
Evaluation		readily biodegradable	

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water			
No	Substance name	CAS no.	EC no.
1	propane	74-98-6	200-827-9
log Pow		appr.	1.8
Method		QSAR	
Source		ECHA	

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The product is not considered to be a PBT.
vPvB assessment	The product is not considered to be a vPvB.

12.6 Other adverse effects

Other adverse effects
Global Warming Potential: 3

12.7 Other information

Other information
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

dispose of in accordance with local regulation.

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Compressed gas packaging under pressure. Do not open by force. Do not heat above 50°C. Dispose of compressed

Trade name: R290- Propane 2.5; Tegan®290, Propane 2.5**Product no.:** R290**Current version :** 1.1.0, issued: 13.05.2020**Replaced version:** 1.0.0, issued: 20.02.2019**Region:** GB

gas packagings only if completely discharged. Do not burn empty compressed gas packagings. Do not pierce, cut or weld uncleaned containers.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class	2
Classification code	2F
Hazard identification no.	23
UN number	UN1978
Proper shipping name	PROPANE
Tunnel restriction code	B/D
Label	2.1 RID: (+13)

14.2 Transport IMDG

Class	2.1
UN number	UN1978
Proper shipping name	PROPANE
EmS	F-D, S-U
Label	2.1

14.3 Transport ICAO-TI / IATA

Class	2.1
UN number	UN1978
Proper shipping name	Propane
Label	2.1

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

To be transported always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of conduct in case of incident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

In accordance with the Reach regulation (EC) 1907/2006, the product does not contain any substances that are considered as subject to listing in annex XIV, inventory of substances requiring authorisation.

REACH candidate list of substances of very high concern (SVHC) for authorisation

In accordance with article 57 and article 59 of the Reach regulation (EC) 1907/2006, this substance is not considered as subject to listing in annex XIV, inventory of substances requiring authorisation ("Authorization list").

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annexe XVII.	No 40
---	-------

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:	P2
--	----

Other regulations

Trade name: R290- Propane 2.5; Tegan®290, Propane 2.5

Product no.: R290

Current version : 1.1.0, issued: 13.05.2020

Replaced version: 1.0.0, issued: 20.02.2019

Region: GB

Adhere to the national sanitary and occupational safety regulations when using this product.

15.2 Chemical safety assessment

A chemical safety assessment has been carried out for this substance.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

U When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Department issuing safety data sheet

UMCO GmbH

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 753969