

Trade name: R443A

Product no.: R443A

Current version : 1.1.0, issued: 13.05.2020

Replaced version: 1.0.0, issued: 20.02.2019

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name

R443A**1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

Industrial Use

Professional use

Refrigerant

Uses advised against

Consumer use

1.3 Details of the supplier of the safety data sheet**Address**

TEGA - Technische Gase und Gasetechnik GmbH

Werner-von-Siemens-Straße 18

97076 Würzburg

Telephone no. +49 931 2093-220

Fax no. +49 931 2093-180

e-mail kaeltemittel@tega.de

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Flam. Gas 1; H220

Press. Gas liq.; H280

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS02



GHS04

Signal word

Danger

Hazard statement(s)

H220

Extremely flammable gas.

Trade name: R443A

Product no.: R443A

Current version : 1.1.0, issued: 13.05.2020

Replaced version: 1.0.0, issued: 20.02.2019

Region: GB

H280 Contains gas under pressure; may explode if heated.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 In case of leakage, eliminate all ignition sources.

P403 Store in a well-ventilated place.

2.3 Other hazards

Contact with the liquid can cause cold burns or frostbite.

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	
1	propene			
	115-07-1 204-062-1 601-011-00-9 01-2119447103-50	Flam. Gas 1; H220 Press. Gas liq.; H280	>= 50.00 - < 70.00	Vol%
2	propane			
	74-98-6 200-827-9 601-003-00-5 01-2119486944-21	Flam. Gas 1; H220 Press. Gas liq.; H280	>= 25.00 - < 50.00	Vol%
3	isobutane			
	75-28-5 200-857-2 601-004-00-0 01-2119485395-27	Flam. Gas 1; H220 Press. Gas liq.; H280	>= 5.00 - < 10.00	Vol%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	U	-	-	-
2	U	-	-	-
3	C, U	-	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

SECTION 4: First aid measures**4.1 Description of first aid measures****General information**

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove affected person from danger area, lay him down. Seek medical advice immediately.

After inhalation

Trade name: R443A**Product no.:** R443A**Current version :** 1.1.0, issued: 13.05.2020**Replaced version:** 1.0.0, issued: 20.02.2019**Region:** GB

Remove affected persons from dangerous area by observing suitable respiratory protection measures. Ensure supply of fresh air. Irregular breathing/no breathing: artificial respiration. Call a doctor immediately.

After skin contact

In case of contact with skin wash off immediately with soap and water. In case of frostbite, rinse with plenty of water. Do not remove clothing.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes).

After ingestion

Rinse mouth thoroughly with water. Do not induce vomiting. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed**Symptoms**

Shortness of breath; Frostbite; respiratory arrest. Unconsciousness

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Extinguishing powder; Water spray jet; Water mist; Foam

Unsuitable extinguishing media

High power water jet; Carbon dioxide

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide and carbon dioxide; May explode if exposed to heat. Liquefied gas: Spilled liquid can cause cold burns. This gas is heavier than air and may accumulate in low areas.

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear full protective suit. Containers close to fire should be transferred to a safe place. Cool closed containers exposed to fire with water. Pressure increase, bursting and explosion hazard during heating. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Ensure adequate ventilation. Keep away from ignition sources. Do not breathe gas. Cordon and mark contaminated area. Remove persons to safety. Risk of explosion.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Avoid release in the environment. Suppress gases/vapours/mists with water spray jet.

6.3 Methods and material for containment and cleaning up

Ensure adequate ventilation. Dispose of absorbed material in accordance with the regulations.

6.4 Reference to other sections

Information regarding safe handling, see chapter 7. Information regarding personal protective measures, see chapter 8. Information regarding waste disposal, see chapter 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Trade name: R443A**Product no.:** R443A**Current version :** 1.1.0, issued: 13.05.2020**Replaced version:** 1.0.0, issued: 20.02.2019**Region:** GB**Advice on safe handling**

Only qualified and trained persons are authorised to handle. Provide good ventilation at the work area (local exhaust ventilation, if necessary). To be used only according to instructions for use. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose containers heat or sources of ignition. In case of accidental release: danger due to low temperature of the liquid product. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Comply with the health and safety at work laws.

General protective and hygiene measures

Wash hands before breaks and after work. Do not inhale gases. Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Have emergency shower available.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Isolate from sources of heat, sparks and open flame. Take precautionary measures against electrostatic loading (earthing necessary during loading operations). Use explosion-proof equipment/fittings and non-sparking tools. Electrical equipment should be protected to the appropriate standard.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Keep container tightly closed in a cool, well-ventilated place, open and handle carefully. Protect from heat and direct sunlight.

Recommended storage temperature

Value < 50 °C

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

Do not store together with: combustible materials; oxidizing agents; oxidizing substances; spontaneously combusting substances; explosive substances

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters**

No parameters available for monitoring.

8.2 Exposure controls**Appropriate engineering controls**

Ensure adequate ventilation, local exhaust at the work station if necessary. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment**Respiratory protection**

Self-contained breathing apparatus. In case of insufficient ventilation or long-term effect use breathing apparatus.

Respiratory filter (gas) : AX

Eye / face protection

Tightly fitting safety glasses (EN 166).

Hand protection

Low-temperature-resistant gloves (EN 511). Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

with 1907/2006/EC

Trade name: R443A

Product no.: R443A

Current version : 1.1.0, issued: 13.05.2020

Replaced version: 1.0.0, issued: 20.02.2019

Region: GB

Other

Chemical-resistant work clothes. Fire-resistant antistatic protective clothing. Protective shoes.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Form/Colour	
liquified gas	
colourless	
Odour	
almost odourless	
Odour threshold	
No data available	
pH value	
No data available	
Boiling point / boiling range	
No data available	
Melting point / melting range	
No data available	
Decomposition point / decomposition range	
No data available	
Flash point	
No data available	
Auto-ignition temperature	
No data available	
Oxidising properties	
No data available	
Explosive properties	
No data available	
Flammability (solid, gas)	
highly flammable	
Source	Analogous
Lower flammability or explosive limits	
No data available	
Upper flammability or explosive limits	
No data available	
Vapour pressure	
No data available	
Vapour density	
Value	1,53
Reference temperature	15 °C
Source	supplier
Comments	Air = 1
Evaporation rate	
No data available	
Relative density	

with 1907/2006/EC

Trade name: R443A

Product no.: R443A

Current version : 1.1.0, issued: 13.05.2020

Replaced version: 1.0.0, issued: 20.02.2019

Region: GB

No data available

Density

No data available

Solubility in water

No data available

Solubility(ies)

No data available

Partition coefficient: n-octanol/water

No	Substance name	CAS no.	EC no.
1	propene	115-07-1	204-062-1
	log Pow		1.77
	Reference temperature		20 °C
	with reference to	pH 7	
	Source	ECHA	
2	propane	74-98-6	200-827-9
	log Pow	appr.	1.8
	Method	QSAR	
	Source	ECHA	
3	isobutane	75-28-5	200-857-2
	log Pow		2.80
	Reference temperature		20 °C
	with reference to	pH 7	
	Source	ECHA	

Viscosity

No data available

9.2 Other information**Other information**

No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

Dangerous reactions are not expected if the product is handled according to its intended use.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

May ignite when exposed to strong oxidising agents. Risk of formation of explosive gas mixtures in air.

10.4 Conditions to avoid

T > 48 °C; Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Oxidizing agents; humidity

10.6 Hazardous decomposition products

None, if handled according to intended use.

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute oral toxicity**

No data available

Acute dermal toxicity

with 1907/2006/EC

Trade name: R443A

Product no.: R443A

Current version : 1.1.0, issued: 13.05.2020

Replaced version: 1.0.0, issued: 20.02.2019

Region: GB

No data available			
Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	propane	74-98-6	200-827-9
LC50	>	800000	ppmV
Duration of exposure		0.25	h
State of aggregation	Gas		
Species	rat		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	isobutane	75-28-5	200-857-2
LC50		520400	ppmV
Duration of exposure		2	h
State of aggregation	Gas		
Species	mouse		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Skin corrosion/irritation			
No data available			
Serious eye damage/irritation			
No data available			
Respiratory or skin sensitisation			
No data available			
Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	propene	115-07-1	204-062-1
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	propane	74-98-6	200-827-9
Route of exposure	inhalational		
Species	Salmonella typhimurium		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	isobutane	75-28-5	200-857-2
Species	Salmonella typhimurium		
Method	Value taken from the literature		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	propene	115-07-1	204-062-1
Route of exposure	inhalational		
Species	rat / mouse		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	propane	74-98-6	200-827-9
Route of exposure	inhalational		
Species	rat		
Method	OECD 422		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	isobutane	75-28-5	200-857-2
Route of exposure	inhalational		
Species	rat		

with 1907/2006/EC

Trade name: R443A

Product no.: R443A

Current version : 1.1.0, issued: 13.05.2020

Replaced version: 1.0.0, issued: 20.02.2019

Region: GB

Method	OECD 422
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Carcinogenicity

No	Substance name	CAS no.	EC no.
1	propene	115-07-1	204-062-1
Route of exposure		inhalational	
Species		rat / mouse	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

STOT - single exposure

No data available

STOT - repeated exposure

No	Substance name	CAS no.	EC no.
1	propene	115-07-1	204-062-1
Route of exposure		inhalational	
Species		rat / mouse	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
2	propane	74-98-6	200-827-9
Route of exposure		inhalational	
Species		rat	
Method		OECD 422	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
3	isobutane	75-28-5	200-857-2
Route of exposure		inhalational	
Species		rat	
Method		OECD 422	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Aspiration hazard

No data available

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	propene	115-07-1	204-062-1
LC50		51.7	mg/l
Duration of exposure		96	h
Species		fish	
Method		QSAR	
Source		ECHA	

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	propene	115-07-1	204-062-1
EC50		28.2	mg/l
Duration of exposure		48	h
Species		Daphnia	
Method		QSAR	

Trade name: R443A

Product no.: R443A

Current version : 1.1.0, issued: 13.05.2020

Replaced version: 1.0.0, issued: 20.02.2019

Region: GB

Source	ECHA
--------	------

Toxicity to Daphnia (chronic)

No data available

Toxicity to algae (acute)

No	Substance name	CAS no.	EC no.
1	propene	115-07-1	204-062-1
EC50		12.1	mg/l
Duration of exposure		96	h
Species	Algae		
Method	QSAR		
Source	ECHA		

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	propane	74-98-6	200-827-9
Type	aerobic biodegradation		
Value		50	%
Duration		3	d
Method	QSAR		
Source	ECHA		
Evaluation	readily biodegradable		
2	isobutane	75-28-5	200-857-2
Type	aerobic biodegradation		
Value		50	%
Duration		3.1	d
Method	QSAR		
Source	ECHA		
Evaluation	readily biodegradable		

Abiotic Degradation

No	Substance name	CAS no.	EC no.
1	propene	115-07-1	204-062-1
Type	Photolysis		
Half-life		14.6	h
Source	ECHA		

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water			
No	Substance name	CAS no.	EC no.
1	propene	115-07-1	204-062-1
log Pow		1.77	
Reference temperature with reference to		20	°C
Source	pH 7 ECHA		
2	propane	74-98-6	200-827-9
log Pow	appr.	1.8	
Method	QSAR		
Source	ECHA		
3	isobutane	75-28-5	200-857-2
log Pow		2.80	
Reference temperature with reference to		20	°C
	pH 7		

with 1907/2006/EC

Trade name: R443A

Product no.: R443A

Current version : 1.1.0, issued: 13.05.2020

Replaced version: 1.0.0, issued: 20.02.2019

Region: GB

Source

ECHA

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment**Results of PBT and vPvB assessment**

PBT assessment

The components of this product are not considered to be a PBT.

vPvB assessment

The components of this product are not considered to be a vPvB.

12.6 Other adverse effects

No data available.

12.7 Other information**Other information**

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

dispose of in accordance with local regulation.

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Compressed gas packaging under pressure. Do not open by force. Do not heat above 50°C. Dispose of compressed gas packagings only if completely discharged. Do not burn empty compressed gas packagings. Do not pierce, cut or weld uncleaned containers.

SECTION 14: Transport information**14.1 Transport ADR/RID/ADN**

Class	2
Classification code	2F
Hazard identification no.	23
UN number	UN3161
Proper shipping name	LIQUEFIED GAS, FLAMMABLE, N.O.S.
Technical name	propene propane
Tunnel restriction code	B/D
Label	2.1 RID: (+ 13)

14.2 Transport IMDG

Class	2.1
UN number	UN3161
Proper shipping name	LIQUEFIED GAS, FLAMMABLE, N.O.S.
Technical name	propene propane
EmS	F-D, S-U
Label	2.1

14.3 Transport ICAO-TI / IATA

Class	2.1
UN number	UN3161
Proper shipping name	Liquefied gas, flammable, n.o.s.
Technical name	propene propane
Label	2.1

14.4 Other information

No data available.

Trade name: R443A

Product no.: R443A

Current version : 1.1.0, issued: 13.05.2020

Replaced version: 1.0.0, issued: 20.02.2019

Region: GB

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

To be transported always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of conduct in case of incident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annexe XVII.	No 40
---	-------

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:	P2
--	----

Other regulations

Adhere to the national sanitary and occupational safety regulations when using this product.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

- C Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- U When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Department issuing safety data sheet

UMCO GmbH

Trade name: R443A

Product no.: R443A

Current version : 1.1.0, issued: 13.05.2020

Replaced version: 1.0.0, issued: 20.02.2019

Region: GB

This information is based on our present knowledge and experience.
The safety data sheet describes products with a view to safety requirements.
It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 753458