

Trade name: R600, Tegan®600, n-Butane 2.5**Product no.:** R600**Current version:** 3.0.0, Revision: 25.06.2026**Replaced version:** 2.1.0, Revision: 04.08.2025**Region:**
GER**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name****R600, Tegan®600, n-Butane 2.5**

Substance name	butane
REACH registration no.	01-2119474691-32

Identification numbers

CAS no.	106-97-8
EC no.	203-448-7
Index no.	601-004-00-0

1.2 Relevant identified uses of the substance or mixture and uses advised against**Relevant identified uses of the substance or mixture**

Industrial Use
Professional use
Formulation of mixtures

Pure chemical
Aerosol
Propellant
Fuel
Consumer use
Refrigerant

Uses advised against

No other use is recommended.

1.3 Details of the supplier of the safety data sheet**Address**

TEGA-Technische Gase und Gasetechnik GmbH
Werner-von-Siemens-Straße 18
97076 Würzburg

Telephone no.	+49 931 2093-220
Fax no.	+49 931 2093-180
e-mail	kaeltmittel@tega.de

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):
+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Flam. Gas 1A; H220
Press. Gas liq.; H280

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3 and 4 of Annex I to CLP.

Trade name: R600, Tegan®600, n-Butane 2.5**Product no.:** R600**Current version:** 3.0.0, Revision: 25.06.2026**Replaced version:** 2.1.0, Revision: 04.08.2025**Region:**
GER

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Product identifier

106-97-8 (butane)

Hazard pictograms

GHS02



GHS04

Signal word

Danger

Hazard statement(s)

H220

Extremely flammable gas.

H280

Contains gas under pressure; may explode if heated.

Precautionary statement(s)

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P377

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381

In case of leakage, eliminate all ignition sources.

P403

Store in a well-ventilated place.

2.3 Other hazards

This product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Contact with the liquid can cause cold burns or frostbite.

PBT assessment

The product is not considered to be a PBT.

vPvB assessment

The product is not considered to be a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical characterization

Substance name butane

Formula C₄H₁₀

Molecular weight 58,12

Identification numbers

CAS no. 106-97-8

EC no. 203-448-7

Index no. 601-004-00-0

Other information

Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
C, U	-	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

3.2 Mixtures

Not applicable. The product is not a mixture.

SECTION 4: First aid measures

Trade name: R600, Tegan®600, n-Butane 2.5

Product no.: R600

Current version: 3.0.0, Revision: 25.06.2026

Replaced version: 2.1.0, Revision: 04.08.2025

Region:
GER

4.1 Description of first aid measures

General information

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove affected person from danger area, lay him down. Seek medical advice immediately.

After inhalation

Remove affected persons from dangerous area by observing suitable respiratory protection measures. Ensure supply of fresh air. Irregular breathing/no breathing: artificial respiration. Call a doctor immediately.

After skin contact

In case of contact with skin wash off immediately with soap and water. In case of frostbite, rinse with plenty of water. Do not remove clothing.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes).

After ingestion

Rinse the mouth thoroughly with water. Do not induce vomiting. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

Shortness of breath; Frostbite; respiratory arrest. Unconsciousness

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguishing powder; Water spray jet; Water mist; Foam

Unsuitable extinguishing media

High power water jet; Carbon dioxide

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide and carbon dioxide; May explode if exposed to heat. Liquefied gas: Spilled liquid can cause cold burns. This gas is heavier than air and may accumulate in low areas.

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear full protective suit. Containers close to fire should be transferred to a safe place. Cool closed containers exposed to fire with water. Pressure increase, bursting and explosion hazard during heating. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Ensure adequate ventilation. Keep away from ignition sources. Do not breathe gas. Cordon and mark contaminated area. Remove persons to safety. Risk of explosion.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Avoid release in the environment. Suppress gases/vapours/mists with water spray jet.

6.3 Methods and material for containment and cleaning up

Ensure adequate ventilation. Dispose of absorbed material in accordance with the regulations.

Trade name: R600, Tegan®600, n-Butane 2.5**Product no.:** R600**Current version:** 3.0.0, Revision: 25.06.2026**Replaced version:** 2.1.0, Revision: 04.08.2025**Region:**
GER

6.4 Reference to other sections

Information regarding safe handling, see section 7. Information regarding personal protective measures, see section 8. Information regarding waste disposal, see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Only qualified and trained persons are authorised to handle. Provide good ventilation at the work area (local exhaust ventilation, if necessary). To be used only according to instructions for use. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose containers heat or sources of ignition. In case of accidental release: danger due to low temperature of the liquid product. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Comply with the health and safety at work laws.

General protective and hygiene measures

Wash hands before breaks and after work. Do not inhale gases. Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Have emergency shower available.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Isolate from sources of heat, sparks and open flame. Take precautionary measures against electrostatic loading (earthing necessary during loading operations). Use explosion-proof equipment/fittings and non-sparking tools. Electrical equipment should be protected to the appropriate standard.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed in a cool, well-ventilated place, open and handle carefully. Protect from heat and direct sunlight.

Recommended storage temperature

Value < 50 °C

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

Do not store together with: combustible materials; oxidizing agents; oxidizing substances; spontaneously combusting substances; explosive substances

Stoarge Class according TRGS 510

2A Gases (except aerosol dispensers and lighters)

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
	TRGS 900		
	Butan		
	WEL long-term (8-hr TWA reference period)	2400	mg/m ³ 1000
	Ceiling Limit	4(II)	ml/m ³

8.2 Exposure controls

Trade name: R600, Tegan®600, n-Butane 2.5**Product no.:** R600**Current version:** 3.0.0, Revision: 25.06.2026**Replaced version:** 2.1.0, Revision: 04.08.2025**Region:**
GER**Appropriate engineering controls**

Ensure adequate ventilation, local exhaust at the work station if necessary. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Personal protective equipment**Respiratory protection**

Self-contained breathing apparatus. In case of insufficient ventilation or long-term effect use breathing apparatus.

Respiratory filter (gas) : AX

Eye / face protection

Tightly fitting safety glasses (EN 166).

Hand protection

Low-temperature-resistant gloves (EN 511). Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material Leather

Other

Chemical-resistant work clothes. Fire-resistant antistatic protective clothing. Protective shoes.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

State of aggregation	
gas	
Form	
liquified gas	
Colour	
colourless	
Odour	
petrol-like	
pH value	
reason for missing pH	substance/mixture is a gas
Source	supplier
Boiling point / boiling range	
Value	-0,5 °C
Source	supplier
Melting point/freezing point	
Value	-138,2 °C
Source	supplier
Decomposition temperature	
Value	435 °C
Flash point	
No data available	
Ignition temperature	
No data available	
Auto-ignition temperature	

Trade name: R600, Tegan®600, n-Butane 2.5**Product no.:** R600**Current version:** 3.0.0, Revision: 25.06.2026**Replaced version:** 2.1.0, Revision: 04.08.2025**Region:**
GER

Value	365 °C
Source	supplier

Explosive properties

May form explosive gas-air mixtures.

Source	supplier
--------	----------

Flammability

highly flammable

Lower explosion limit

Value	1,4 % vol
Source	supplier

Upper explosion limit

Value	9,5 % vol
Source	supplier

Vapour pressure

Value	242,65 kPa
Reference temperature	25 °C
Source	supplier

Relative vapour density

Value	2,07
Reference temperature	0 °C
Source	supplier
Comments	Air = 1

Relative density

Value	0,6012
Reference temperature	0 °C
Source	supplier

Density

No data available

Solubility in water

Value	88 mg/l
Source	supplier

Solubility

No data available

Partition coefficient n-octanol/water (log value)

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
log Pow		1,09	
Reference temperature		20 °C	
with reference to		pH 7	
Source		ECHA	

Kinematic viscosity

Value	0,007 mPa*s
Reference temperature	20 °C
Type	dynamic
Source	supplier

Particle characteristics

Not applicable

Source	supplier
--------	----------

9.2 Other information

Trade name: R600, Tegan®600, n-Butane 2.5**Product no.:** R600**Current version:** 3.0.0, Revision: 25.06.2026**Replaced version:** 2.1.0, Revision: 04.08.2025**Region:**
GER**Other information**

No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

Dangerous reactions are not expected if the product is handled according to its intended use.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

May ignite when exposed to strong oxydising agents. Risk of formation of explosive gas mixtures in air.

10.4 Conditions to avoid

T > 48 °C; Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Oxidizing agents; humidity

10.6 Hazardous decomposition products

None, if handled according to intended use.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity**

No data available

Acute dermal toxicity

No data available

Acute inhalational toxicity

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
LC50		539600	ppmV
Duration of exposure		4	h
State of aggregation	Gas		
Species	mouse		
with reference to	isomereic mixture		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Skin corrosion/irritation

No data available

Serious eye damage/irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
Type of examination	In vitro Mammalian Chromosomal Aberration Test		
Species	Human Lymphocyte		
Method	OECD 473		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Type of examination	in vitro gene mutation study in bacteria		
Species	Salmonella typhimurium TA98, TA100, TA1535, TA1537		

Trade name: R600, Tegan®600, n-Butane 2.5**Product no.:** R600**Current version:** 3.0.0, Revision: 25.06.2026**Replaced version:** 2.1.0, Revision: 04.08.2025**Region:**
GER

Method	OECD 471
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Reproduction toxicity

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
Route of exposure	inhalational		
NOAEC		9000	ppm
Type of examination	Reproduction/Developmental Toxicity Screening Test		
Species	rat		
Method	OECD 422		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Carcinogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
Route of exposure	inhalational		
NOAEC		9000	ppm
Species	rat		
Method	OECD 422		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Aspiration hazard

No data available

11.2 Information on other hazards**Endocrine disrupting properties**

No data available

Other information

No data available.

SECTION 12: Ecological information**12.1 Toxicity****Toxicity to fish (acute)**

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
LC50	appr.	25,4	mg/l
Duration of exposure		96	h
Species	fish		
Method	QSAR		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Toxicity to fish (chronic)

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
NOEC	appr.	1,8	mg/l
Duration of exposure		30	day(s)
Species	fish		
Method	(Q)SAR		

Trade name: R600, Tegan®600, n-Butane 2.5

Product no.: R600

Current version: 3.0.0, Revision: 25.06.2026

Replaced version: 2.1.0, Revision: 04.08.2025

Region:
GER

Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Toxicity to Daphnia (acute)

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
EC50	appr.	14,8	mg/l
Duration of exposure		48	h
Species	Daphnia		
Method	QSAR		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Toxicity to Daphnia (chronic)

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
NOEC	appr.	1,1	mg/l
Duration of exposure		30	day(s)
Species	Daphnia		
Method	QSAR		
Source	ECHA		

Toxicity to algae (acute)

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
EC50	appr.	12,4	mg/l
Duration of exposure		96	h
Species	Green algae		
Method	QSAR		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability**Biodegradability**

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
Type	aerobic biodegradation		
Value		50	%
Duration		3,46	d
Method	QSAR		
Source	ECHA		

12.3 Bioaccumulative potential**Partition coefficient n-octanol/water (log value)**

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
log Pow		1,09	
Reference temperature		20	°C
with reference to	pH 7		
Source	ECHA		

12.4 Mobility in soil**Results of PMT and vPvM assessment**

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7

Trade name: R600, Tegan®600, n-Butane 2.5**Product no.:** R600**Current version:** 3.0.0, Revision: 25.06.2026**Replaced version:** 2.1.0, Revision: 04.08.2025**Region:**
GER

PMT assessment	The substance is not PMT.
vPvM assessment	The substance is not vPvM.
Source	ECHA

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment		
Product Name		
R600, Tegan®600, n-Butane 2.5		
PBT assessment	The product is not considered to be a PBT.	
vPvB assessment	The product is not considered to be a vPvB.	
Source	supplier	
No	Substance name	CAS no.
1	butane	106-97-8
EC no.	203-448-7	
PBT assessment	The substance is not PBT.	
vPvB assessment	The substance is not vPvB.	
Source	ECHA	

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

Other adverse effects
Global warming potential within 100 years: 0

12.8 Other information

Other information
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

dispose of in accordance with local regulation.

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Compressed gas packaging under pressure. Do not open by force. Do not heat above 50°C. Dispose of compressed gas packagings only if completely discharged. Do not burn empty compressed gas packagings. Do not pierce, cut or weld uncleaned containers.

SECTION 14: Transport information**14.1 UN number or ID number**

ADR/RID/ADN	UN1011
IMDG	UN1011
ICAO-TI / IATA	UN1011

14.2 UN proper shipping name

ADR/RID/ADN	BUTANE
IMDG	BUTANE
ICAO-TI / IATA	Butane

14.3 Transport hazard class(es)

ADR/RID/ADN - Class	2
Label	2.1 RID: (+13)
Classification code	2F
Tunnel restriction code	B/D
Hazard identification no.	23

Trade name: R600, Tegan®600, n-Butane 2.5**Product no.:** R600**Current version:** 3.0.0, Revision: 25.06.2026**Replaced version:** 2.1.0, Revision: 04.08.2025**Region:**
GER

IMDG - Class	2.1
Label	2.1
ICAO-TI / IATA - Class	2.1
Label	2.1

14.4 Packing group

ADR/RID/ADN	-
IMDG	-
ICAO-TI / IATA	-

14.5 Environmental hazards

EmS	F-D, S-U
-----	----------

14.6 Special precautions for user

To be transported always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of conduct in case of incident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

In accordance with the REACH regulation (EC) 1907/2006, the product does not contain any substances that are considered as subject to listing in annex XIV, inventory of substances requiring authorisation.

REACH candidate list of substances of very high concern (SVHC) for authorisation

In accordance with article 57 and article 59 of the Reach regulation (EC) 1907/2006, this substance is not considered as subject to listing in annex XIV, inventory of substances requiring authorisation ("Authorization list").

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 40
--	-------

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:	P2
--	----

Other regulations

Adhere to the national sanitary and occupational safety regulations when using this product.

National regulations**Water Hazard Class (Germany)**

Class	nwg
Identification number	561
Source	Classification according to AwSV (Regulation on facilities for handling substances that are hazardous to water).

Other regulations

Take into account: TRGS 510 "Storage of hazardous substances in non-stationary containers"

15.2 Chemical safety assessment

A chemical safety assessment has been carried out for this substance.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

Trade name: R600, Tegan®600, n-Butane 2.5

Product no.: R600

Current version: 3.0.0, Revision: 25.06.2026

Replaced version: 2.1.0, Revision: 04.08.2025

Region:
GER

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3 and 4 of Annex I to CLP.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

- | | |
|---|--|
| C | Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers. |
| U | When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. |

Creation of the safety data sheet

UMCO GmbH

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

This document is an English translation of the legally compliant safety data sheet of the region Germany. This document, including UFI and emergency telephone number, may only be used for placing on the market in the region Germany.

Copyright-protected document. Any changes or reproductions require the express consent of UMCO GmbH.

Prod-ID 754029